

EDDK - Tower

Runways

The airport has three runways, two of which run parallel and one of which crosses two runways.

Runway 13L / 31R

Runway 13L/31R is the longest runway at 3815 x 60m and is primary used for all inbound and outbound traffic. Runway 31R and 13L are both equipped with ILS CAT III.

Runway 13R / 31L

At a distance of about 1km southwest of runway 13L/31R is the much shorter parallel runway 13R/31L, which is 1863 x 45m long.

Due to its length and technical equipment, this runway is preferably used for VFR traffic. Because of its proximity to the military section, it is also frequently used by military aircraft. Runway 13R/31L is only approved for aircraft up to code C (e.g. B739, A321). During high traffic situations, this runway can be used for all light and medium traffic that is able (TORA 1863 m).

For **non-precision approaches** to runway 13R, a flight and ground visibility of at least 2.1 km must be provided due to the shortened approach lighting.

Runway 06 / 24

Across runways 13/31 is the intersecting runway 06/24, measuring 2459 x 45m. Only landing direction 24 is equipped with an ILS (CAT I). For RWY 06 only non-precision approaches are available.

Runway 06/24 is only approved for aircraft up to code letter E, including the B748.

For **non-precision approaches** to runway 24, a flight and ground visibility of at least 1.5 km must be provided due to the obstacle situation.

RWY24 can be used to taxi aircraft as well. Either because of wingspan limitations on TWY D or to the military apron, as well as for aircraft landing RWY13L to vacate the runway and to avoid the sharp turn into A3.

Hospitals: Several hospitals with helipads are located in the urban area of Cologne.

In the extended centerline of runway 13L, approx. 1.5 km north of the NDB LJ, is the hospital Merheim. Approaches to runway 13L fly over the hospital at approx. 1500ft. Helicopters may approach the landing area below the approaching traffic. Appropriate traffic information must then be provided to avoid missed approaches.

On the north-western edge of the control zone in Cologne-Nippes, on the CTR boundary, is the rather seldom approached St. Vinzenz Hospital.

On the west side in the Lindenthal district, just outside the control zone, is the University Hospital of Cologne.

To the west of the control zone is the Nörvenich ETNN airbase. Despite their proximity, the control zones of the two airports do not border directly on each other, but are separated by a narrow strip of type C airspace.

VFR-Traffic

There are 7 mandatory reporting points and 1 optional reporting point available for VFR traffic at Cologne.

Reporting Point	Location
NOVEMBER 1	BAB 4, exit Bergisch Gladbach-Bensberg
NOVEMBER 2	BAB 3, motorway service station Königsforst-Ost
ECHO 1	Church in the middle of Neunkirchen
ECHO 2 (Optional)	BAB 3, service area Sülztal
SIERRA 1	Marina at the mouth of the Sieg River into the Rhine
SIERRA 2	Sports facilities north of the village of Troisdorf-Spich
KILO 1	BAB 1 / BAB 57, motorway interchange Köln-Nord
KILO 2	BAB 4, rhine bridge Rodenkirchen

VFR Routings: The most popular VFR route through the control zone follows the Rhine along the Cologne Cathedral and the Old Town and connects the mandatory reporting points S1, K2 and K1.

Just as popular for flights from / to the Bergisches Land are take-offs or landings in Bonn-Hangelar combined with a flight through the control zone via the S and N routes.

VFR Squawk: All VFR traffic inside the controlzone of Cologne will get the transpondercode **7003**.

Helicopter traffic: The airport has frequent helicopter traffic. On the one hand, this is due to the fact that a helicopter squadron of the Federal Police is located at Bonn-Hangelar Airport and training traffic also takes place there. On the other hand, two rescue helicopters are stationed at the airport. "Christoph 3" (CHX3) has its landing pad at the GAT, while the intensive care transport helicopter "Christoph Rheinland" (CHX75) of the ADAC has its base at the north-western edge of the V- Apron towards Taxiway B. Only "Christoph 3" though, is allowed to land and depart directly from it's helipad. Every other helicopter has to either land on the runway or the runway threshold (e.g. 13R) and has to air-taxi to it's final position afterwards.

Direction of Operation

Up to a tailwind component of 5kt, operations will be handled via runways 31R and 31L. Runway 24 is also used if necessary up to a tailwind component of 5kt.

Operating direction 06 is used extremely rarely because the wind through the Cologne Bay preferably blows from a northerly to northwesterly direction.

In order to accelerate the taxiing of traffic and after prior coordination with ground control, the tower may give taxiing traffic (taxiways A3-A4) an initial taxi instruction into taxiway A or taxiway E (depending on the take-off direction) and then hand it over to ground control. Most commonly, tower will give an initial right turn on E, to hold short of A5.

Parallel Operations

Due to the distance of only approx. 1150 m between the runway centrelines of 13L/31R and 13R/31L, independent parallel runway operations between these runways for IFR and/or SVFR traffic are not permitted.

Radar and runway separation need to be applied, wake turbulence separation is not required.

Seperation and Spacing:

Depending on the amount of departures, Köln Tower may request arrivals to runway 31/13 with 5 or 6 miles. Coordination is required if more spacing is needed.

Targetspacing for inbounds only need to be applied by Arrival when **requested by Tower!**
Otherwise radar or WTC separation is used by default.

Note: In order to maintain separation Köln Tower may reduce aircraft after transfer of communication.

While not necessary, it is recommended to only use speed control after prior coordination with the Arrival Controller.

Reduced runway separation

RRS minima may be applied by Köln/Bonn Tower, according to the following table:

Runway	preceding CAT 1/CAT 2 succeeding CAT 1	preceding CAT 1/CAT 2 succeeding CAT 2	preceding CAT 3 succeeding CAT 1/CAT 2/CAT 3
13L/31R	600m	1500m	2400m
13R/31L	600m	N/A	N/A
06/24	600m	1500m	N/A

RECAT-EU procedures

According to new wake turbulence minimum separation values established by Eurocontrol, the familiar categories established by the ICAO (Light, Medium, Heavy, Super) have been divided into new sub-categories, thus offering the possibility of separating aircraft in certain categories even more closely.

The DFS has decided to apply the procedure at Cologne Bonn, but only in the “Lower Heavy/Lower Heavy” category and restricted to aircraft types A300, B757 and B767.

This means that two consecutive aircraft (**WTC H**) can be separated by 3 miles and do not have to be separated by 4 miles, as required by ICAO guidelines, if the preceding aircraft is one of the of the above-mentioned aircraft type. For further information: [RECAT-EU](#)

Missed Approaches

For all published approaches, missed approaches will be executed as published unless otherwise coordinated.

EDDK Tower has to ensure initial separation between departures and between departures and missed approaches. He therefore may take action to ensure or reestablish separation. Radar shall be informed immediately of the action taken. Transfer of Communication then takes place, once separation is established. Missed Approaches should be transferred to Feeder (DKAT), if not otherwise coordinated. The next departure requires a departure release.

Crossing Runway Operations

Combined operation of runways 13L/31R and 24 has the highest capacity. When runway 13R/31L is used as well, runway 24 is blocked for significantly longer.

It is important during crossing runway operations that the preceeding traffic (landing or departing) has crossed the runway cross before the succeeding traffic (landing) for the other runway has reached the 1 NM final. Otherwise the succeeding traffic has to go around.

Example: Departing traffic runway 31R has passed the runway cross before the inbound reaches 1 NM final for runway 24.

Nörvenich sector A

If the military approach sector for Nörvenich (ETNN) has activated sector A, **NVO SID's out of runways 24 and 31, as well as COL departures out of runway 24 may no longer depart. Coordination with DKA required.**

Usually, this sector will only be active for short periods of time to allow TNNA to vector arriving traffic to final approach during 24 operations at ETNN; however, when there is local IFR traffic at ETNN, the sector may be activated for longer periods.

After coordination with DKA NVO outbounds should be recleared to runway 13 or, on a different SID (e.g. COL/WYP) to expect vectors to NVO after departure.

DKA (or TNNA, if DKA is offline) **will inform Tower when sector A is activated and deactivated.**

Transfer of Communication "Auto Handoff":

Köln/Bonn utilizes an auto-handoff procedure for IFR departures where **Tower will not hand off outbounds to the arrival controller.** Make sure to set the correct departure frequency in the ATIS.

Outbounds should contact APP **when passing 2.000 ft MSL** unless explicitly told to remain on Tower frequency.

